

MARKED-UP SPECIFICATION

TITLE: COMMUNICATION SYSTEM, TRANSMITTER, RECEIVER, AND
METHOD UTILIZING A DATA STORAGE DESCRIPTOR

INVENTOR(S): LAURENT HERRMANN

SERIAL NO.: 09/935,259

ATTY. DOCKET NO.: PHFR 000084



COMMUNICATION SYSTEM, TRANSMITTER, RECEIVER, AND
METHOD UTILIZING A DATA STORAGE DESCRIPTOR

BACKGROUND OF THE INVENTION

Field Of The Invention

[0001] The invention relates to a communication system between a transmitter and a receiver, ~~which the transmitter transmits~~
5 transmitting digital data and data descriptors to the receiver via a communication channel.

[0002] ~~It~~ The invention has numerous applications in communication systems for multimedia data in which a point-to-point architecture is implemented, or more generally a client/server
10 architecture.

Description Of The Related Art

[0003] ~~The PCT document published under no. International Patent Application No.~~ WO 98/03016 describes a method and a system for
15 sending digital data from a transmitter to a receiver over a unidirectional communication channel. The receiver receives the digital data which are collected and locally stored on the basis of criteria reflecting a user profile, such that the data thus stored can subsequently be used by the user at the receiver end.

20 [0004] The storage method for the data sent by the transmitter as used in the prior-art document has a certain number of limitations.

[0005] First of all, the selection of the data stored at the receiver end renders necessary the use of a user profile at the receiver end which permits of retaining only those data which correspond to the various criteria contained in said profile. If the receiver is used by different users, it is necessary a priori to have available as many profiles as there are users, which, on the one hand, means that sufficient memory space must be available for storing the profiles, and, on the other hand, requires means for readily changing over to another user profile. This selection method, which is not very flexible in use, accordingly implies the use of expensive means.

[0006] Secondly, the use of a user profile for selecting the data has limitations. In fact, a user profile never contains a full representation of the preferences of a user but, instead, contains general preferences, so that it is not improbable that certain data received at the receiver end and corresponding to preferences of the user are not selected for storage, because they have not been included in the user profile. In that case, a data not stored locally but of interest to the user, such that he/she wants to consult it, will have to be sent by the transmitter, which involves a risk of saturating the communication channel and of not having the data immediately available.

SUMMARY OF THE INVENTION

[0007] The invention has for its object to counteract these limitations to a high degree by proposing a communication system, a receiver, as well as a method, which have the object of associating descriptors with data sent by the transmitter so as to identify, at the receiver end in a manner more reliable and less expensive than that described in the prior-art document, those data which are to be ~~steeked~~stored and which are capable of a multiple use.

[0008] This invention may advantageously be used if data to be sent by the transmitter correspond to data of text type, audio type (e.g., encoded according to the MPEG-2 or MPE3 audio standards), or video type (e.g., encoded according to the MPEG-2, MPEG-4 or H.263 video standards).

[0009] To achieve this object, the present invention is characterized in that the transmitter comprises:

[0010] - analysis means for analyzing digital data so as to identify data referred to as multiple-use data which can be used several times at the receiver end, and data referred to as single-use data which can be used only once upon reception at the receiver end,

[0011] - creation means for creating data descriptors for describing each multiple-use data previously identified, said descriptors comprising a set of characterizing fields, and

[0012] - insertion means for inserting the data descriptors in the set of multiple-use data, each multiple-use data being then associated with a data descriptor.

[0013] The invention is also characterized in that the receiver comprises:

[0014] - analysis means for analyzing received data so as to detect the presence of descriptors of multiple-use data and thus to
5 identify multiple-use data and single-use data,

[0015] - storage means for storing detected multiple-use data and their associated descriptors previously received,

[0016] - composition means for composing the contents of an application on the basis of single-use data and multiple-use data
10 previously stored, a same data which has a multiple use in the composition of said contents being then directly recovered upon each use from said storage means by recovery means.

[0017] Such a communication system, in contrast to the system described in the prior-art document, in which the selection of the
15 data capable of a multiple use is made at the receiver level, provides an identification of the multiple-use data at the transmitter end by means of data descriptors inserted into the data flow sent by the transmitter to the receiver. The data flow received at the receiver end is then analyzed so as to detect the
20 presence of data descriptors which indicate the presence of multiple-use data. Whenever such a descriptor is detected, it is locally stored at the receiver end together with the data to which it relates. The multiple-use data thus stored may be used from that moment on not only immediately following their reception at the

receiver end, but also later without the necessity of requesting for them to be sent from the transmitter.

[0018] According to a further characteristic of the invention,

the descriptors and the corresponding data, both stored locally,

5 are permanently made available so as to take into account not only the current processing capacities of the receiver but also various temporal parameters characteristic of each stored multiple-use data.

10

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] These as well as other, more detailed aspects of the invention will be clarified further in the following description with reference to the annexed drawings, all by way of example to which the invention is not limited, wherein:

15

[0020] Fig. 1 is a block diagram of an example of a communication system comprising a transmitter and a receiver according to the invention_{7i}

[0021] Fig. 2 shows the structure of the descriptors of the data according to the invention_{7i}

20

[0022] Fig. 3 shows the structure of a first data descriptor according to the invention by way of example_{7i}

[0023] Fig. 4 shows the structure of a second data descriptor according to the invention by way of example_{7i}

[0024] Fig. 5 shows the structure of a third data descriptor

25

according to the invention by way of example_{7i}

[0025] Fig. 6 is a diagram showing the operation of a receiver according to the invention in detail,—; and

[0026] Fig. 7 shows a communication system according to the invention between a server and a number of terminals.

5

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0027] Fig. 1 represents a communication system according to the invention comprising a transmitter 101 and a receiver 102 which are in communication via a communication channel 103.

10 The transmitter comprises—

———— a data source 104 which generates various data such as data of the audio, video, text, or image type—

————, analysis means 105 for analyzing each of the data 104 and classifying them into two categories, on the one hand, the multiple-use data 106 capable of a multiple utilization at the receiver end 102, and, on the other hand, the single-use data 107 which will basically be used once only at the receiver end.

Multiple-use data are detected, for example—, after an a-priori or a priori selection depending on the type of said multiple-use data, or other identification parameters. This classification may be implemented, for example, by anticipating the requests of a user present at the receiver end 102. For example, if the data 104 relate to video trailers of TV programs, it is highly probable that these data will be used several times at the receiver end, for which reason they are classified as data 106. On the other hand, if

the data 104 relate to a very specific content which is not likely to be used several times at the receiver end, they will be classified among the data 107.

[0028] —The transmitter 101 further comprises creation means
 5 108 for creating data descriptors for multiple-use data. The ~~functional block~~creation means 108 creates a data descriptor with multiple fields 109 for each of the multiple-use data 106, each field being characteristic of the data under consideration. The descriptor acts not only as an identifier for the multiple-use
 10 data, but also characterizes them, especially with a view to facilitating their handling and control at the receiver end.

[0029] —~~i~~Insertion means 110 is included in the transmitter 101
 for inserting each descriptor 109 in the data flow 106. Each multiple-use data 106 is thus associated with its descriptor 109,
 15 for example, through concatenation of the data 106 with the data 109. The new data flux 111 thus generated at the output of the insertion means 110 is accordingly formed by a sequence of multiple-use data/descriptor data twins.

[0030] —~~a~~A multiplexing unit 112 for multiplexes the data 111
 20 and 107, ~~which are multiplexed~~ so as to deliver the data flow 113, which then comprises a succession of single-use data and data twins of descriptors and multiple-use data. This multiplexing may be, for example, compliant with the MPEG-2 Transport Stream standard.

—————a A transport layer 114 for interfacinginterfaces the
 25 transmitter with the communication channel 103 and ~~for~~

~~delivering~~delivers a data flow 115 sent to the receiver 102 via the communication channel 103 on the basis of the multiplexed data 113.

[0031] The receiver 102 comprises:

_____ a transport layer 116 ~~which receives~~for receiving the
5 data flow 115 and ~~for generates~~generating the data flow 117,
_____ and analysis means 118 for detecting the multiple-use
data 119 and the single-use data 120 in the data flow 117. For this
purpose, the data descriptors 109, which were strung together with
the multiple-use data at the transmitter end, are detected~~—~~, i.e.,
10 if such a descriptor present in the data flow 117 is effectively
detected by the analysis means 118, this will reveal the presence
of a multiple-use data to which it is attached. If no data
descriptor is detected, all data contained in the data flow 117 are
classified as single-use data.

15 [0032] —sStorage means 121 is included in the receiver for
storing multiple-use data and their associated descriptors. For
example, the data descriptor/multiple-use data twins may be stored
on a disc or in a memory. It may also be envisaged to store
separately multiple-use data on a first storage means, and the
20 corresponding data descriptors on a second storage means.

_____ The receiver also includes composition means 122 for
composing a content for an application on the basis of stored
multiple-use data 119 and single-use data 120. For example, the
composition means may correspond to a navigator for multimedia data
25 by means of which a user has a possibility of interacting via the

access 123 so as to modify the contents of the application and to call up specific data in which he or she has an interest. A search is carried out via the access 124 among all the multiple-use data previously stored for each request 123 indicating a user's wish to

5 consult a particular data, so as to verify whether this particular data has not yet been previously stored. If it appears that this data has been previously stored, it is sent directly to the composition unit 122 via the path 125 for taking part in the composition of a novel content without the necessity of having it

10 sent from the transmitter. If this particular data is not present among the data stored in storage means 121, and the communication channel 103 comprises a return path 128 between the receiver 102 and the transmitter 101, a request 126 ~~will be~~is sent via the transport layer 116 to the transmitter, ~~then this time~~ via said

15 return path 128 towards the transmitter 101, the latter then sending to the receiver the missing data via the path 115 so that this data can be used in the composition of the content. If the particular data is not present among the data stored in storage means 121 and the communication channel 103 does not comprise a

20 return path 128, the user's demand cannot be satisfied. Whenever a new content relating to single-use data is created, these are used directly upon their detection in the data flow 117, and no storage space is reserved for them, in contrast to the multiple-use data, which are immediately stored in storage means 121 and then used in

25 the composition of the content. Since the multiple-use data are

systematically stored, they are readily available from then on at any moment if the composition unit 122 needs them for the creation of a new content. This renders it possible not only to refrain from demanding data from the transmitter 101, which could overburden the communication channel 103, but also to improve the availability of the data at the level of the receiver by giving the latter a high degree of operational autonomy. To avoid the storage of multiple-use data which are not useful and take up space, the invention provides means for making these data apparent, which means will be explained with reference to Fig. 3.

[0033] —Finally, the receiver 102 includes visualization means 127 for making a content of multimedia data visible, such as a video screen which enables a user to see and interact with a content composed by the navigator 122.

[0034] Fig. 2 shows the structure of the data descriptors according to the invention. These descriptors, as was noted above, are inserted at the transmitter level for each so-called multiple-use data which may be used several times at the receiver end. These descriptors serve, on the one hand, to identify the multiple-use data received by the receiver so that it will store them locally, and, on the other hand, to inform the receiver of the characteristics of these multiple-use data by means of various fields so that the receiver can carry out operations for making the stored multiple-use data visible.

[0035] The structure of the data descriptor according to the invention, given by way of example here, comprises five fields:

[0036] ~~the~~ field 21 corresponds to an identifier, for example a digital one, which renders it possible to differentiate the descriptors from one another and thus to avoid any confusion;

[0037] ~~the~~ field 22 gives information on the type of data to which the descriptor belongs. For example, the field may indicate to the receiver that data of the audio, video, or image type are concerned. If the receiver is not capable of processing a certain type of information, for example if the video format cannot be decoded owing to the absence of suitable processing means, this information provided by the field 22 will prove useful because the corresponding data will not be stored so as not to occupy storage space of the receiver unnecessarily;

[0038] ~~the~~ field 23 is a time value given in relation to a time reference such as a local clock situated at the receiver end. This value is a starting time indicating to the receiver from what moment the data to which the descriptor is attached can be used. Let us assume that multiple-use data corresponding, for example, to trailers of video films programmed for an entire week have been stored on the receiver, and a user can consult these data by means of an electronic program guide (EPG). If the EPG can only present the video data of the present day, for example because of equipment limitations, only those video data will be made active and accordingly capable of consultation whose associated descriptor

fields 23 have a date corresponding to the current date. If this is not the case, the data for which the field 23 of the associated descriptor is a date corresponding to subsequent days will not be made active. In concrete terms, a video data will be rendered
 5 active in that it is decoded in such a manner that it is quickly accessible and usable whenever the user wants to consult it-;

[0039] —~~the~~ field 24 is a time value given in relation to a time reference such as a local clock situated at the receiver end. This value is an end date indicating to the receiver from what
 10 moment the data to which the descriptor is attached will no longer have to be stored by the receiver. Taking the example of the multiple-use data corresponding to film trailers again, the field 24 of each descriptor will correspond to the end date of the film to which it is attached. In other words, the field 24 corresponds
 15 to the end date of the validity of the data to which it is attached-; and

[0040] —~~the~~ field 25 is a time value corresponding to the maximum duration for storage of the data on the receiver. This field renders possible a data management in a time different to
 20 that controlled by the fields 23 and 24. This field 25 applies more particularly to multiple-use data which do not have an absolute time reference. Starting from the moment the multiple-use data is received at the receiver, the storage duration is calculated and compared with that of the field 25 so as to comply with the maximum
 25 duration of storage.

[0041] Figs. 3, 4, and 5 give examples of descriptors according to the invention for which the various fields have been completed.

[0042] Fig. 3 shows the structure of a descriptor relating to an audio-type data. This descriptor, according to the invention, is identified by the digit 8 and relates to a data valid up to the date 3600, which absolute date is expressed in the time unit current for the receiver and in relation to a time reference of this same receiver.

[0043] Fig. 4 shows the structure of a descriptor relating to a video-type data. This descriptor, according to the invention, is identified by the digit 9 and relates to a data valid between the dates 3600 and 10,800, ~~which these~~ absolute dates are being expressed in the time unit current for the receiver and in relation to a time reference of this same receiver.

[0044] Fig. 5 shows the structure of a descriptor relating to an image-type data. This descriptor, according to the invention, is identified by the number 10 and relates to a data valid for a duration of 86,400, starting from its reception by the receiver, ~~which this~~ absolute time is being expressed in the time unit current for the receiver and in relation to a time reference of this same receiver.

[0045] Fig. 6 is a diagram representing the operation of a receiver according to the invention as described with reference to Fig. 1 in detail. This diagram relates more particularly to the system for making available the multiple-use data and their

associated descriptors stored locally for subsequent use. As was noted above, the data accompanied by a data descriptor whose structure is similar to that of Fig. 1, are added to the data referred to as multiple-use data which can be used several times by a user at the receiver end. These multiple-use data 119 are locally stored in the receiver in a storage unit 121, and, similarly, their associated descriptors 602 are stored in the storage unit 601.

[0046] Immediately after their initial storage in the unit 601, the descriptors are analyzed by way of their various fields so as to verify that the data to which they belong are compatible with the capacities 603 of the receiver and that these data can be effectively used at the receiver end. For example, capacities 603 of the receiver may be stored locally in a storage means on said receptor. For this purpose, the means 604 for making the data available ~~check and verify~~ checks and verifies the compatibility of the fields 22 of each descriptor with the capacities 603 of the receiver. For example, if the receiver cannot process video-type data, the data 119 and their associated descriptor 602 of the video type will not be stored, or will be temporally stored and immediately erased from the units 601 and 121.

[0047] After the compatibility of the multiple-use data with the processing capacity of the receiver has been verified, the data 119 are periodically updated by the means 604. This updating has for its object in particular to erase the data 119 which are judged to be useless, or to render them active so that they can be quickly

available and readily usable for the creation, for example, of a multimedia content. For this purpose, the time fields 23, 24, and 25 of the descriptors 602 are periodically compared with a local clock 605 belonging to the receiver for ensuring that the validity end date corresponding to the field 24 has not been reached, or
5 that the validity duration corresponding to the fields 25 has not elapsed, which, in the opposite case, would have the result that the corresponding descriptors and their attached data are erased. Similarly, the validity start date corresponding to the field 23 is
10 periodically compared with the clock 605 so as to prepare the data which are about to be used. For this purpose, a preparation means device 606 ~~are~~ is provided for enabling a preparation of the stored data 119, ~~which the preparation means are device being~~ controlled by decision commands 607 generated following a comparison between
15 the field 23 and the clock 605. For example, if a multiple-use data 119 corresponds to a compressed video which can be consulted starting from a moment of validity t1, a preparation command 607 will be generated some time before this moment t1 such that this video data can be decompressed by the preparation device 606,
20 whereupon the decompressed video will replace the compressed video in the storage unit 121. If a user interacting via the request 123 with the contents of the application created at the composition unit level 122 wishes to consult a particular data, and if this data is recognized as being a data already stored locally, the
25 command 124 is given to deliver this data over the path 125 to the

contents composition unit 122. If this is a video-type data, it is thus interesting that it should be quickly available, i.e., decompressed.

[0048] If a user wishes to consult a particular data, all means
5 may be activated for determining whether this data corresponds to a locally stored data or not. It is, in fact, possible that a user requires access to a multiple-use data erased from the storage units 601 and 121. Generally speaking, it will suffice to search in the set of descriptors 602 whether a descriptor identical to that
10 of the desired data exists. If this is the case, the data is extracted from the storage unit, if it is not, the user request is not honored. For example, comparison means may be used to compare the descriptor of a particular data with the overall set of data descriptors previously stored on the receiver, for deducing whether
15 said particular can be retrieved.

[0049] ~~This~~ Fig. 6 only shows the processing of multiple-use data, the single-use data being processed in a conventional manner as they arrive at the receiver as a function of its processing capacity.

20 [0050] Fig. 7 shows an example of a communication system according to the invention. This communication system corresponds, for example, to a system used in a broadcast context between a server (i.e., transmitter) and a set of clients (i.e., receivers). The system is composed of a server 71 which communicates with n
25 terminals 72 via a set of n communication channels 73. The server

performs the part of a transmitter as described above, sending single-use data and multiple-use data accompanied by their data descriptors. In a so-called distributed application, the same data are sent to the set of terminals 72. These terminals act as
5 receivers as described above, locally storing each and every multiple-use data identified as such in the data flow transmitted through the channels 73. Since each terminal is capable of receiving requests for data from a user via the access 74, the requests relating to multiple-use data stored locally are honored
10 in that the corresponding data are delivered from the storage unit situated at the terminal in question.

[0051] A communication system between a transmitter and a receiver capable of identifying and storing at the receiver end those data which can be used several times by an application has
15 thus been described. Numerous modifications may indeed be applied to the embodiments described without departing from the scope of the invention. It may, in particular, be envisaged to use a user profile in conjunction with the data retrieval means situated at the receiver such that only certain multiple-use data are retained.
20 Moreover, additional fields may be added to the data descriptors of the multiple-use data so as to characterize more precisely those data to which they are attached. In particular, descriptors as described according to the invention may advantageously be used in a standard dedicated to data description, such as the MPEG-7
25 standard.

PHFR 000084

[0052] As regards the constructional implementation of such a communication system, use will be made of signal processors both at the transmitter end and at the receiver end, said processors carrying out the various operations described above on the digital
5 data flows by carrying out instructions stored in a memory.

ABSTRACT+ OF THE DISCLOSURE

~~The invention relates to~~In a communication system between
a transmitter and a receiver, ~~which the~~ transmitter transmits
5 digital data via a communication channel to the receiver. Such a
communication system provides an identification of the data which
are capable of a multiple-use at the level of the transmitter by
means of data descriptors inserted in the data flow sent from the
transmitter to the receiver. The data flow received at the receiver
10 end is then analyzed so as to detect the presence of data
descriptors indicating the presence of multiple-use data. Whenever
such a descriptor is detected, it is locally stored at the level of
the receiver together with the data to which it relates. The
multiple-use data thus stored may then be used not only immediately
15 after their reception at the receiver end, but also subsequently
without the necessity of requesting them from the transmitter.

~~Application: Data descriptor.~~

~~Fig. 1~~